

tesapack[®] BASIC Packaging tape

BNR 53390, 58570, 58571, 58572, 58573, 58574, 58575

Product Features

- Dimensions: 66m:50mm / 50m:45mm / 40m:45mm * Solvent free * UV- and age-resistance * Easy unwinding

Product Description

The tesa[®] BASIC Packaging Tape makes sealing your boxes and cartons easy. The tape easily unwinds, is solvent-free and resistant to both UV light and aging. Thus, you can rely on it sticking to and securing your packages for a long time – whether you're shipping a package to a friend or perhaps back to an online shop.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | BOPP | • Total thickness | 41 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|----------------|---------------------|-----------|
| • Adhesive strength | Light adhesion | • Solvent free | yes |
| • Ageing resistance (UV) | yes | • Suitable surfaces | Cardboard |
| • Applicationfield | Office, Home | • Tear resistance | yes |
| • Hand tearability | no | • Tensile strength | 38 N/cm |
| • Low noise unwinding | no | | |

tesapack[®] BASIC

Packaging tape

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=53390>